## 3M<sup>™</sup> Premium Clear Masking Film 80139



- Premium formulation minimises the risk of marking on damp vehicles
- Translucent purple film maintains visibility of the repair area
- Fold pattern enables easy application by one person




## 3M<sup>™</sup> Premium Clear Masking Film 80139

Premium Clear Masking Film is a high-density polyethylene sheeting designed for the prevention of overspray damage during a repair. Special surface treatments ensure excellent adhesion of paint to the film around the repair area, and eliminate the

need for additional paper masking, as well as the risk of paint 'flaking' on removal.

New Premium Clear Masking Film 80139 uses advanced technology that minimises the risk of imprint marking or

'ghosting' when used to mask damp vehicles.



The static cling properties of the film, and its 4 metre width (folded to 1 metre on the mobile dispenser) allow a rapid, one person application.

The static cling holds every contour of the vehicle to eliminate overspray reaching the vehicle under the film.



Inset picture shows the ghosting effect that can occur with normal film in damp conditions

## Instructions for use

Position the dispenser horizontally at either end of the vehicle and pull the film sheeting from the bottom of the roll centrally along the car. From beside the car, reach underneath to the fold and pull out edge of the sheeting to cover the car.

A triangular 3M logo is printed along the centre of the sheeting to provide an accurate positional guide. To ensure that the treated side of the film is facing outward to take the paint overspray, the 3M logo should read correctly and should not be reversed. The triangle logo design allows assessment of correct placement from any angle.

Part No	Item
80139	Premium Clear Masking Film (4m x 150m)
06780	3M Mobile Masking Film Dispenser
07813	3M Masking Film Cutter



Automotive Aftermarket, 3M United Kingdom PLC,

Tel: 016 1237 6391 Fax: 016 1237 5911 aadenquiries.uk@mmm.com Automotive Aftermarket, 3M Ireland,

Tel: (01) 280 3555 Fax: (01) 280 3509 AB 609

EL57